


# DEPLOYMENT OF DATA SONDES FROM FISHING PIERS TO MONITOR NEARSHORE HYPOXIA IN LONG BAY, SOUTH CAROLINA

Susan Libes, J. Michael Trapp, and Scott Kindelberger

Burroughs & Chapin Center for Marine and Wetland Studies, Coastal Carolina University, P.O. Box 261954, Conway, South Carolina 29528-6054



### Hypoxia Discovered in Long Bay, SC

- Long Bay is a shallow coastal embayment bounded in the North by the Cape Fear River and in the south by Winyah Bay (Figure 1).
- The Grand Strand covers 57 km of Long Bay's coastline and houses beachfront tourist destinations such as Myrtle Beach.
- The Grand Strand collectively hosts 15 million visitors per year and hence has become highly urbanized.




Fig. 1. Long Bay lies on the inner continental shelf of the South Atlantic Bight of the USA. The general area over which hypoxia is being observed is shaded in gray. Developed lands are shown in red, forested and wetlands in green and agricultural lands in orange (NOAA Coastal Change Analysis Program 2005). Bathymetric data: NOAA Geophysical Data Center.

Fig. 2. Local press coverage of hypoxia in Long Bay and impact on recreational fisheries

- Dissolved oxygen levels were not being monitored in Long Bay at the time that hypoxic conditions were first discovered.
- Hypoxic conditions were first discovered in July 2004 during a flounder jubilee (Figure 2).
- A monitoring program was initiated in 2006 at the seaward ends of two fishing piers that project about 1000 feet offshore.





ND STA

## Monitoring Program

- Surface and bottom monitoring of dissolved oxygen, salinity and temperature began in 2006 at the Apache and Springmaid fishing piers (Figure 3).
- Data reported every 15 min to online data portal.
- Waters are generally undersaturated with respect to DO during summer months (Figure 4)
- Anoxic conditions were observed in Aug and Sept 2009 (Figure 5).




Fig. 3. Apache Family Campground Fishing Pier

Constrained mixing hypothesis for

Terrestrial inputs (nutrients & organic matter)

Outfall pipes, swashes, ocean outfalls

preventing dispersion of inputs

Rivers, inlets, groundwater

Non-hypoxic conditions

**Hypoxic conditions** 

the formation of hypoxia in Long Bay

 $\frac{-2.0}{2.5}$ 






Fig. 5. Water quality sonde continuous

oxygen at Apache pier. Red line marks overall mean values.



YSI Datasondo

- tides following periods of upwelling favorable winds (out of the southwest.)
- Modest degree of stable vertical temperature stratification was present.
- Lowest DO coincided with flooding



Local inputs widely dispersed in coastal ocean Low concentration = Low DO consumption rates Southwest winds cause upwelling of bottom water Bottom water intrusion acts as a physical barrier

#### Inputs concentrate inshore Elevated concentrations greatly stimulate DO consumption rates leading to localized hypoxia

# Figure 6













Radon-222 levels

of low DO

increase during periods

Supports constrained


Suggests groundwater

Long Bay Hypoxia Monitoring

Consortium and financial supporters

inputs are significant.


mixing hypothesis



constrained mixing and groundwater inputs to Long Bay.

## Novel Deployment of Monitoring Gear

- YSI 600 OMS and 6600 EDS data sondes deployed on stainless steel ziplines in water depths of 5 to 7 m in nearshore just seawater of surf zone
- Surface sonde maintained ~1m below the surface using counterweights
- Bottom sonde ~1m above the bottom
- Vaisala WXT520 weather station
- Lightening protection includes pom-pom diffusers.
- Data transmitted every 15 min to YSI Econet for display on public web portal http://www.ysieconet.com/public/WebUI/Default.aspx?hidCustomerID=131
- Biofouling requires cleaning 3 times a week during summer months.
- Field QC includes pre and post deployment comparison with manually deployed sonde. In-situ accuracy  $\pm$  0.4 mg/L for DO and  $\pm$ 0.25 psu for
- Secchi depths also measured.
- Data QC'd using Aquarius software from Aquatic Informatics
- Funded monitoring at Cherry Grove (North Myrtle Beach), and Second
- Adds turbidity, pH and chlorophyll sensors
- Funds ,radon (Rn-222) detectors in bottom water to document
- Funds larval recruitment study to document effects of low DO on biota.



Radon-222 detector on pier deck. Bottom water is pumped to the detector.

### Figure 8. Low DO events in May 2011

- Red arrows mark periods of low temperature and concurrent low DO
- Wind speeds were below 10 mph during each of
- these events. Wind direction was
- upwelling favorable preceding these events. Lowest DO was observed
- during flooding tides. Low DO events occur as abrupt transitions suggesting advection of low DO water masses past the sondes.

Rn data provided by Dr. R. Peterson, CCU











2012 National Water Quality Monitoring Conference 30 Apr – 4 May, Portland, Oregon, USA